

PROFESSIONAL WOODCARE FOR FLOORING

Lacquer, oil, cleaning & maintenance
for commercial, residential & sport



JUNCKERS

Walking on Danish design

JUNCKERS.IE



W A L K I N G O N D A N I S H D E S I G N

WHY JUNCKERS

By choosing Junckers Wood Care you receive not only a product perfectly suited for surface treatment and protection of wooden floors, you are also drawing upon the expertise we have gained from our manufacture of solid hardwood floors since the 1930's.

The production of Junckers lacquers began in the 1950's and continues today at our main manufacturing plant in Denmark.

Our range of lacquers and oils has always been developed by our own technical and research teams using the best and most up to date materials and technology.

**TOTAL SOLUTIONS,
ALWAYS
ACCOMPANIED BY
PROFESSIONAL
TECHNICAL SUPPORT**

Junckers Wood Care range includes a fully integrated range of products for regular maintenance, refurbishment or surface treatment of brand new wooden floors, meaning that we provide a 100% solution regardless of project type.

We produce Wood Care products specially developed for residential, commercial and sports areas.

All our products are designed to help maintain a healthy indoor climate, be kind to the environment and to complement timber as a natural raw material. This means that our customer will get the full environmental and health benefits which hardwood floors offer.

CONTENTS

- 4** FILLER AND PRIMING PRODUCTS
- 6** FLOOR LACQUERS FOR COMMERCIAL AND RESIDENTIAL USE
- 8** SPORT AND DANCE
- FLOOR LACQUERS & MAINTENANCE PRODUCTS
- 10** OIL AND HARDWAX OIL
- 12** CLEANING, MAINTENANCE PRODUCTS AND ACCESSORIES
- 14** GENERAL INFORMATION
- CLEANING AND MAINTENANCE

During manufacture of Junckers Wood Care Solutions we use stringent quality control throughout. Our policy never to compromise on the quality of materials means that customers will always get the most durable and beautiful finish possible and contractors can be confident that they will be giving their customers the best possible result.

Finally, with Junckers as a professional partner you are sure to receive the correct technical support before, during and after a project. Junckers professional technical team together with our trained sales staff are always ready to assist you and help to ensure the successful completion of your project.

FILLER & PRIMING

Junckers filler and priming products form the basis for creating the most durable surface for a wooden floor. The products are always used in combination with a Junckers top-seal as part of our complete lacquer systems.

FILLER



	JUNCKERS PREFILL	JUNCKERS BASEFILL
i DESCRIPTION	<p>A water-based acrylic filler base for filling gaps Mixed with sanding dust from the sanded floor. It is used for filling small gaps in floors.</p> <p>PreFill is quick drying and is to be used in combination with Junckers water-based priming and floor-finishing products.</p> <p>PreFill is the ultimate water-based solution for floors made of wood species sensitive to changes in humidity.</p>	<p>A quick-drying solvent-based filler for filling larger gaps Mixed with sanding dust from the sanded floor. It is used for filling gaps up to 2mm wide.</p> <p>BaseFill is used in combination with Junckers solvent-based or water-based lacquers, and is suitable for most sanded and untreated parquet floors, including most exotic wood floors.</p>
e APPEARANCE	Creamy/milky. When mixed with sanding dust it dries to the same colour as the wood.	Colourless. When mixed with sanding dust it dries to the same colour as the wood.
🪥 COVERAGE	5-20 m ² /litre depending on the condition of the floor.	10 m ² /litre.
🪥 PACKAGE SIZE	5 litres.	5 and 10 litres.
L DRYING TIME*	45-90 minutes.	Approx. 15 minutes.
🪥 APPLICATION	Broad full-edged spatula stainless steel.	Broad full-edged spatula stainless steel.



*at 20°C and 50% RH



JUNCKERS PRELAK CLEAR / WHITE

JUNCKERS BASEPRIME

<p>i DESCRIPTION</p>	<p>One-component water-based primer Minimises side-bonding for all wooden floors.</p> <p>PreLak dries quickly and is easy to sand.</p> <p>PreLak can be used with Junckers 1-pack and 2-pack water based finishes.</p>	<p>An oil-based very fast curing primer For wooden floors where water-based primers cannot be used due to poor adhesion, for example exotic and oily timbers.</p> <p>BasePrime gives the floor more depth of colour and should only be used directly on to bare wood.</p>
<p>👁 APPEARANCE</p>	<p>PreLak Clear: Creamy/milky. Dries up to a clear finish. PreLak White: Creamy/milky. Dries up to a transparent white finish.</p>	<p>Clear finish.</p>
<p>📏 COVERAGE</p>	<p>PreLak Clear : 8 m²/litre. PreLak White: 10 m²/litre.</p>	<p>10 m²/litre.</p>
<p>📦 PACKAGE SIZE</p>	<p>PreLak Clear: 5 and 10 litres. PreLak White: 5 Litres</p>	<p>5 and 10 litres.</p>
<p>🕒 DRYING TIME*</p>	<p>PreLak Clear: Approx. 1-2 hours. PreLak White: Approx. 4 hours.</p>	<p>Approx. 30 minutes.</p>
<p>🔧 APPLICATION</p>	<p>Short hair roller.</p>	<p>Brush or short-pile varnishing roller.</p>

FLOOR LACQUER FOR

FOR COMMERCIAL & RESIDENTIAL USE

Junckers offers a wide range of floor lacquers which have been specifically developed for residential and commercial use. The choice of product depends on expected levels of foot traffic. The wide choice of sheen levels makes it possible to obtain a finish which exactly suits your individual interior space. When lacquering floors which have been sanded to bare wood, use one of Junckers primers prior to applying the top coats of lacquer. This will help to prevent any gluing effect between the floor boards.



	JUNCKERS PROFINISH	JUNCKERS STRONG	JUNCKERS STRONG PREMIUM
i DESCRIPTION	<p>One-component water-based co polymer acrylic/polyurethane lacquer</p> <p>Fast drying and curing lacquer for normal everyday residential use.</p> <p>Non yellowing and excellent clarity even on dark coloured floors.</p> <p>Suitable for previously sealed as well as on new or fully sanded floors.</p>	<p>One-component water-based co polymer polyurethane/acrylic lacquer</p> <p>Low odour lacquer for wooden floors in heavy traffic residential areas and lighter traffic commercial floors.</p> <p>Offers the ease of use of a one-component product with excellent leveling and flow characteristics.</p> <p>Ideal for use on previously sealed and untreated floors.</p>	<p>One-component water-based 100% polyurethane lacquer</p> <p>Low odour and the toughest one-component lacquer on the market.</p> <p>Non yellowing and excellent clarity even on dark coloured floors.</p> <p>Suitable for previously sealed as well as on new or fully sanded floors.</p>
e APPEARANCE	Creamy/milky in container. Colourless film when dry.	Creamy/milky in the container. Colourless film when dry.	Creamy/milky in the container. Colourless film when dry.
★ GLOSS LEVEL	10) Ultra Matt 20) Matt 50) Silk Matt 80) Gloss	10) Ultra Matt 20) Matt 50) Silk Matt 80) Gloss	{10) Ultra Matt 20) Matt 50) Silk Matt
👉 COVERAGE	10-12 m ² /litre.	10 m ² /litre.	10-12 m ² /litre.
🗑 PACKAGE SIZE	5 litres.	5 litres.	5 litres.
L DRYING TIME*	4 hours. Fully cured after 72 hours. Important! Apply maximum 2 coats per day.	3 hours. Fully cured after 72 hours. Important! Apply maximum 2 coats per day.	3 hours. Fully cured after 72 hours. Important! Apply maximum 2 coats per day.
🔧 APPLICATION	Brush, short haired mohair roller, air/airless spray.	Brush, roller, air/airless spray. Don't apply by pouring out the lacquer directly on the floor.	Brush, roller, air/airless spray. Don't apply by pouring out the lacquer directly on the floor.

*at 20°C and 50% RH

ADDED DURABILITY WITH TWO-COMPONENT LACQUERS

Junckers two-component lacquers are particularly well-suited for high traffic areas. Our HP range sets the standard for just how durable water based lacquers can be, and the fast drying time of the product makes it a perfect choice when time is all important. Junckers range of HP floor lacquers sets the standard in today's market, achieving the highest degree of wear resistance, and superior levelling properties over all other similar two-component water based products on the market.



JUNCKERS PROTECH

One-component oil based lacquer for professional use

Provides a tough and hard wearing finish for machine sanded or untreated wooden floors.

Compared to other oil based products ProTech is easy and pleasant to use due to its low odour.

Highlights the warmer and richer colours in the wood, similar to Oil, but with the benefits of a lacquer finish.

JUNCKERS PROFESSIONAL 625

Two-component acid curing lacquer with very high chemical resistance

For professional use on wooden floors in high traffic commercial, and residential areas.

Can be used on untreated wooden or previously sanded floors to obtain a deep colour lacquered finish.

JUNCKERS HP COMMERCIAL

Premium quality two-component water-based 100% polyurethane lacquer

For use in very high traffic areas and is exceptionally durable and scuff resistant.

Non-yellowing, very fast curing and ready for use the following day.

Must be mixed with HP Commercial Hardener before use.

JUNCKERS HP FRICTION+

A slip resistant two-component non yellowing water based 100% polyurethane lacquer, based upon our HP Commercial lacquer

Fast curing and ideal for use in high traffic areas where slip resistance is important, eg. restaurants and bars.

Must be used as the final coat only.

Must be mixed with Junckers HP Friction+ Hardener before use.

Tested to BS7976-2:2002.



Colourless film when dry.

(20) Matt
(50) Silk Matt

8-10 m²/litre.

2½, 5, and 10 litres.

Approx. 6-8 hours.
Light traffic: 24 hours.
Maximum hardness achieved after one week.

Brush, mohair roller,
air/airless spray.

Colourless film when dry.

(20) Matt
(50) Silk Matt
(80) Gloss

10 m²/ litre

5.2 (5 + 0.2) litres

Recoating: 1½ hours.
Light traffic: 24 hours.
Fully cured after 3 days,

Brush, mohair roller, air/
airless spray.

Creamy/milky in container.
Colourless film when dry.

(10) Ultra Matt
(20) Matt
(50) Silk Matt

10-12 m²/litre.

4.95 litres.
(4½ litres and 0.45 litres)

Touch dry/recoating:
Approx. 3 hours.
Ready for light traffic: 8
hours. Fully cured after 3
days.

Brush, short haired mohair
roller, air/airless spray.

Creamy/milky in container.
Colourless film when dry.

(10) Ultra Matt

10-12 m²/litre.

4.95 litres.
(4½ litres and 0.45 litres)

Touch dry/recoating:
Approx. 3 hours.
Ready for light traffic: 8
hours. Fully cured after 3
days.

Brush, short haired mohair
roller, air/airless spray.

LACQUER & MAINTENANCE

FOR SPORTS FLOORS

Junckers two-component HP Sport lacquer is unequalled in quality and performance and is used on sports floors all over the world including Olympic and Commonwealth Games venues. It is very hard wearing and highly resistant to abrasion and scuffs. Along with our HP SportsLine paint the Junckers HP Sport range provides a complete system for refurbishment and maintenance of sports floors.

LACQUER FOR
SPORTS FLOORS



JUNCKERS HP SPORT

JUNCKERS HP SPORTSLINE



DESCRIPTION

Our premium quality two-component water-based 100% polyurethane lacquer for very high traffic sports floors.

Non-yellowing, extremely durable and scuff resistant, and very fast curing, so the floor is ready for use the next day.

Complies with the friction requirements of EN 14904 for multi-purpose sports floors.

Must be mixed with Junckers HP Sport Hardener before use.

Water based two-component product for painting court markings and other areas in gymnasiums and sports halls.

Recommended for use on floors coated with Junckers HP Sport and on Junckers pre-finished lacquered floors.



APPEARANCE

Creamy/milky in container. Colourless film when dry.

White, yellow, red, blue, green, black.



GLOSS LEVEL/ COLOURS

(50) Silk Matt
(20) Matt

-



COVERAGE

10-12 m²/litre.

6-8 m²/litre.



PACKAGE SIZE

4.95 litres (4½ litres + 0.45 litres)

2,3 litres (2 + 0.3 litres)



DRYING TIME*

Touch dry/recoating: approx. 3 hours. Ready for light traffic: 8 hours. Fully cured after 3 days.

Recoating: 24 hours. Ready for light traffic: 8 hours. Fully cured after 3 days.



APPLICATION

Brush, short haired roller, air/air-less spray.

Brush, short haired mohair roller or applicator.

*at 20°C and 50% RH

JUNCKERS HP SPORTSLINE - LINE MARKING PAINT

Approved according to EN 14904. After installation the sports floor only needs line markings and for this Junckers HP SportsLine is the perfect solution.

Junckers water-based line marking paint is available in white, red, green, blue, yellow and black. Colours may be mixed to provide more colours.

MAINTENANCE FOR
SPORTS FLOORS



JUNCKERS SYLVASPORT CLEANER

JUNCKERS SYLVADISSOLVER H₂O



DESCRIPTION

Universal cleaner for lacquered hardwood sports floors.

SylvaSport Cleaner does not leave a surface residue and is therefore ideal for regular use.

To neutralize SylvaSport Cleaner and maintain slip resistance, use SylvaNeutralizer.

SylvaDissolver is a cleaner for removal of resin from lacquered wooden sports floors.

The product is used to soften handball resin before regular cleaning.



MIXING PROPORTIONS

50-200 ml to 10 litres of water

1 to 20 parts of water. Very dirty floors 1 to 10 parts of water.



COVERAGE

-

-



PH-VALUE

Diluted: Approx. 6-8.
Undiluted: Approx. 8.5

Undiluted: Approx. 11.
Diluted: Approx. 8.



PACKAGE SIZE

5 litres.

5 and 10 litres.



DRYING TIME*

-

-



APPLICATION

Well wrung cloth or mop.

By sponge, cloth or mop. Cloth and atomizer or scrubber dryer machine



PUMP

1 litres:
¼ pump

1 litres:
¼ pump

5 litres:
2 pumps

5 litres:
2 pumps

10 litres:
4 pumps

10 litres:
4 pumps

LACQUER AND MAINTENANCE

OIL & HARDWAX OIL

Junckers Oils and Hardwax Oil add a beautiful deep sheen and superior wear resistance to the floor. Choose either a clear oil, which emphasizes the natural character of the wood, or one of our range of coloured oils, which allow you to create a unique look to your room or interior.

If you like the appearance of the oil, but want the advantages of a lacquered surface too, then you can combine Junckers HP Oil or Rustic Oil Colour with HP Commercial lacquer.

Junckers Oils are for interior use only.

OIL AND HARDWAX OIL




	JUNCKERS RUSTIC OIL CLEAR	JUNCKERS RUSTIC SOLID 100	JUNCKERS PROFESSIONAL HARDWAX OIL
i DESCRIPTION	<p>Priming and finishing oil for untreated wooden floors and table-/worktops.</p> <p>Rustic Oil Clear can be used in combination with Rustic Oil Colour.</p>	<p>Priming and finishing oil for untreated/sanded wooden floors and table-/worktops.</p> <p>Very low content of VOC, only 15 g/l.</p>	<p>Priming and finishing Hardwax Oil for untreated/sanded wooden floors.</p> <p>Gives the floor a deep lustre and rich colour and is perfect for residential or commercial areas.</p> <p>Also ideal for use in locations where minimum closure time is important.</p> <p>Hardwax Oil cannot be overcoated with water-based lacquers.</p>
👁 APPEARANCE	Clear – gives the wood a deep, warm glow.	Gives the wood a deep, warm glow.	Matt to Ultra matt.
📏 COVERAGE	10-50 m ² /litre depending on wood structure and absorption.	Absorbing wood species: approx. 7.5 m ² per litre. Less absorbing wood species: approx. 15 m ² per litre.	20-30 m ² /litre.
📦 PACKAGE SIZE	¾, 2½, 5, 10, 25 and 200 litres.	2½, 5 and 10 litres.	5 litres.
🕒 DRYING TIME*	16-24 hours before applying the finishing coat. Ready for use 24 hours after the finishing coat. Fully cured after 3 days.	Minimum 16 hours. Ready for use 24 hours after the finishing treatment. Fully cured after 3 days.	Dry to touch at least 4 hours. Recoating approx. 6 hours. Buffing approx. 16 hours. Fully cured after 6 days.
🔧 APPLICATION	Cloth, brush, roller, lambswool applicator or spray in combination with a nylon scouring pad for all types of surfaces.	Shorthaired roller in a medium thick layer.	Roller, brush or stainless steel spatula.

*at 20°C and 50% RH

JUNCKERS RUSTIC OIL COLOUR

With our coloured oils, you can give the floor a whole new look and create an exciting atmosphere.


Coloured oils are slightly transparent and emphasize the natural grain structure of the wood.



TIO

**JUNCKERS
RUSTIC OIL COLOUR**

 DESCRIPTION	Indoor priming and finishing oil product for untreated wooden floors and table-/worktops.
 APPEARANCE	Coloured liquid that dries to a transparent coloured surface. The colour Invisible retains an untreated look on light wood species. Invisible is not recommended on dark wood species.
 COVERAGE	10-50 m ² depending on wood structure and absorption.
 PACKAGE SIZE	0.375 and 2.5 litre. White and black also 0,75 and 5 litre. Cherry also 0,75 litre.
 DRYING TIME*	16-24 hours before applying the finishing oil. Ready for use 24 hours after the finishing treatment. Fully cured after 3 days.
 APPLICATION	Cloth, brush, roller or lambswool applicator in combination with a nylon scouring pad for all types of surfaces.



CLEANING & MAINTENANCE

CLEANING



JUNCKERS SYLVACLEANER

JUNCKERS SYLVANEUTRALIZER

 DESCRIPTION	<p>SylvaCleaner is a universal cleaning product for daily or periodic cleaning of lacquered and oiled wood floors.</p> <p>SylvaCleaner has been developed to dissolve surface dirt and to dry quickly.</p> <p>SylvaCleaner does not leave a film or residue on the floor.</p>	<p>Junckers SylvaNeutralizer is used for cleaning wood floor surfaces before maintaining with lacquer or oil.</p> <p>SylvaNeutralizer dries quickly and neutralises the surface after cleaning with SylvaCleaner. It is not necessary to clean the floor afterwards with water.</p>
 APPEARANCE	Colourless.	Colourless.
 PH-VALUE	Diluted: Approx. 6-8 Undiluted: Approx. 8.5	Diluted: 3 Undiluted: 2
 MIXING PROPORTIONS	50–200 ml per 10 litres of water.	200 ml per 10 litres of water.
 PACKAGE SIZE	1, 2½ and 5 litres.	1 litre.
 DRYING TIME*	Approx. 5 minutes.	Approx. 5 minutes.
 APPLICATION	Well wrung out cloth or mop.	Well wrung out cloth or mop.
 PUMPS	<p> 1 litres: ¼ pump</p> <p> 5 litres: 2 pumps</p> <p> 10 litres: 4 pumps</p>	<p> 1 litres: ¼ pump</p> <p> 5 litres: 2 pumps</p> <p> 10 litres: 4 pumps</p>

*at 20°C and 50% RH

MAINTENANCE



JUNCKERS RUSTIC TOP OIL



DESCRIPTION

A surface maintainer for use on floors which have been treated with Junckers Rustic Oil.

TopOil is easy to apply and fast drying so the floor is ready for use after 30 to 60 minutes.

TopOil protects the surface, restores a uniform sheen to the floor and reduces the effects of scratches and abrasions.

Apply a coat of this oil, before starting to use a factory oiled Black Oak floor.



APPEARANCE

Dries to colourless ultra matt appearance.



GLOSS LEVEL

Ultra Matt



COVERAGE

30-50 m² per litre.



PACKAGE SIZE

Black: 2.5 litres.
Clear: 1, 2½ and 10 litres.



DRYING TIME*

Ready for light traffic after 30-60 minutes.
Fully cured after 24 hours.




APPLICATION

Flat floor mop or cotton cloth.

ACCESSORIES



Junckers Premium Aqua 25 roller
10 pcs. per box



Junckers roller frame
10 pcs. per box

Junckers Telescopic roller pole

GENERAL INFORMATION - CLEANING & MAINTENANCE

LACQUERED FLOORS

Junckers prefinished lacquered floors have a very hard-wearing factory applied polyurethane lacquer surface, and normally require no treatment prior to use.

The life span of the lacquer largely depends on proper cleaning and maintenance. In some high traffic commercial areas and/or those subject to spillage, consideration should be given to a further coat of Junckers lacquer to give extra protection to the floor.

REGULAR CLEANING

Vacuum and/or sweep the floor to remove surface dust and grit. Clean the floor with a mild solution of Junckers SylvaCleaner, using a well wrung out cloth or a hand held sprayer and flat mop kit.

For larger floors use a scrubber dryer machine using correct mix of SylvaCleaner. Newly lacquered floors should not be cleaned for at least 72 hours after lacquering.

USE OF WATER!

Always use as little water as possible for cleaning.

Use a well wrung out cloth or mop and remove excess water immediately.

Wipe up any spillage of water as soon as possible to prevent the wood becoming damaged.

An extra coat of seal can reduce the likelihood water damage.

LONG TERM MAINTENANCE

Junckers recommends a 12-24 month inspection after installation of the floor to assess its condition and the likely maintenance requirements for the future.

If the surface is very dull and worn then a coat of Junckers lacquer may be required to maintain protection of the floor.

HOW TO MAINTAIN THE FLOOR

The floor should first be cleaned with Junckers SylvaCleaner, then abraded. After removing the dust the floor must be resealed with the appropriate Junckers floor lacquer.

Note that abrading and cleaning are crucial to allow the new coatings to adhere properly.

WAX/POLISHED FLOORS!

Floors previously treated with wax or polish must be machine- sanded before resealing.

JUNCKERS APPROVED CONTRACTORS

Please contact Junckers for a list of approved maintenance contractors who can undertake 12-24 month inspections and resealing work to a high standard.

Junckers is also able to provide contact details for its network of approved distributors and stockists who can supply the complete range of Junckers lacquers, oils and cleaning products.

FURTHER TECHNICAL INFORMATION

See junckers.co.uk / junckers.ie

OIL TREATED FLOORS

Junckers prefinished oiled floors have a factory applied finish, and are ready for use immediately after installation. If any minor scratches and scuffs have occurred during installation, follow the procedure described under "Spot Repair".

CLEANING & MAINTENANCE - DAILY/WEEKLY

Vacuum or sweep the floor to remove surface dust and grit. Clean the floor when required with Junckers SylvaCleaner. Use a well wrung out cloth or a hand held sprayer in combination with a rotary polishing machine mounted with a soft (white) nylon pad. Alternatively a cleaning machine may be used.

USE OF WATER!

Always use as little water as possible for cleaning.

Use a well wrung out cloth or mop and remove excess water immediately.

Wipe up any spillage of water as soon as possible to prevent the wood becoming damaged.

An extra coat of seal can reduce the likelihood water damage.

LONGER TERM MAINTENANCE

1. Clean extremely dirty floors with a black nylon scrubbing pad slightly wetted with a solution of Junckers SylvaCleaner.

Treat only 2-3 m² at a time and wipe up the dirty water immediately. Repeat if necessary until the floor is clean.

2. Apply a coat of Junckers Rustic Oil using a long handled brush or a spray. 1 litre covers approx. 50-100m².
3. After approximately 5 minutes, apply more oil to any matt or dry-looking areas.. Oil from wetter areas may be wiped onto drier looking parts of the floor.
4. After a maximum of 30 minutes of soaking time wipe away any surplus oil with a clean, dry cloth.
5. Buff the floor using a soft nylon pad wrapped with a clean cloth until the surface has a uniform sheen.
6. leave the floor to dry for 16 to 24 hours before use.

PERIODIC MAINTENANCE

1. Clean the floor thoroughly with Junckers SylvaNeutralizer and ensure the floor is allowed to dry completely. If the floor is very worn or dirty follow the routine under "Longer Term Maintenance".
2. Abrade the floor with a black nylon buffing pad or 150 grit mesh disc.
3. Apply a thin coat of Junckers Rustic TopOil on the surface, depending upon the range of oils used.
4. Leave the floor to dry.
5. Repeat the application of Junckers Rustic TopOil if the surface is still dull and patchy.

SPOT REPAIR

Scratches: apply Junckers Rustic TopOil with a soft cloth.

Deep scratches: apply Junckers Rustic Oil as described under "Longer Term Maintenance", sections 2-4.

MAKE SURE THE FLOOR IS DRY

Do not cover freshly oiled floors with plastic or other types of non-porous protection as this will prevent the oil from curing properly.

WAX/POLISHED FLOORS

Oiled floors which have been treated with wax or polish must be machine-sanded before treatment with Junckers Rustic Oil products.



JUNCKERS

Walking on Danish design

JUNCKERS LIMITED
UNITED KINGDOM · Tel. 01376 534 700 · junckers.co.uk
IRELAND · Tel. +353 1 462 2580 · junckers.ie